


# MET / EXTERNAL SEALING CONNECTION TOOL

Manual twist sealing connection tool for external threads.

**CONNECTS TO:**



**SPECIFICATIONS**

Pressure Rating	Operating Temperatures	Materials of Construction
Vacuum to 10,000 psi (689 bar)	-40°F to +200°F (-40°C to +93°C)	Stainless Steel
Termination Port		Seal Material*
NPT, SAE 37° Flare		Urethane

\* Additional seal material types available, consult factory.

**ACTUATION METHOD**

**Manual Twist:** Finger-tight connection eliminates tape and sealants

**ICON™ TECHNOLOGY**

Consult Factory


**ACCESSORIES**

Visit [fastestinc.com](http://fastestinc.com)

- 1** Pressure assisted sealing eliminates leaks and resists movement under pressure
- 2** Leak-tight seal prevents contamination of media and reduces scrap and test damage
- 3** Available in flow or cap versions
- 4** Quick and easy seal replacement to minimize down time, maintenance, and tool inventory

# MET / EXTERNAL CONNECTIONS / NPT THREADS

Swivel Style  
Swivel Style for High Pressure



Ordering Information					Dimensions		
Connects To	Part Number*	Main Seal Package (5)	Rebuild Kit	Pressure Rating	A	B	T**

**NPT | Swivel Style**

1/8 NPT	MET021022	S1105U70	METR02	5000 (345)	1.51 (38.4)	0.80 (20.3)	1/8 MNPT
1/4 NPT	MET041042	S1108U70	METR04		1.74 (44.2)	0.93 (23.6)	1/4 MNPT
3/8 NPT	MET061062	S1110U70	METR06	4000 (276)	1.78 (45.2)	1.20 (30.5)	3/8 MNPT
1/2 NPT	MET081082	S1112U70	METR08		2.05 (52.1)	1.36 (34.5)	1/2 MNPT
3/4 NPT	MET121122	S1115U70	METR12	4000 (276)	2.34 (59.4)	1.68 (42.7)	3/4 MNPT
1 NPT	MET161162	S1212U70	METR16		2.74 (69.6)	1.99 (50.5)	1 MNPT
1-1/4 NPT	MET201202	S1217U70	METR20	2500 (172)	3.27 (83.1)	2.37 (60.2)	1-1/4 MNPT
1-1/2 NPT	MET241161	METB24	METR24	1000 (67)	3.27 (83.1)	2.50 (63.5)	1 FNPT
2 NPT	MET321161	METB32	METR32	750 (52)	2.53 (64.3)	3.00 (76.2)	
2-1/2 NPT	MET401161	METB40	METR40	500 (34)	2.54 (64.5)	3.40 (86.4)	
3 NPT	MET481161	METB48	METR48		2.61 (66.3)	4.25 (108.0)	

**NPT | Swivel Style for High Pressure**

1/8 NPT	METH021022	S1105U70	METR02	10,000 (689)	1.51 (38.4)	0.80 (20.3)	1/8 MNPT
1/4 NPT	METH041042	S1108U70	METR04	8000 (522)	1.74 (44.2)	0.93 (23.6)	1/4 MNPT
3/8 NPT	METH061062	S1110U70	METR06		1.78 (45.2)	1.20 (30.5)	3/8 MNPT
1/2 NPT	METH081082	S1112U70	METR08	6000 (414)	2.05 (52.1)	1.36 (34.5)	1/2 MNPT
3/4 NPT	METH121122	S1115U70	METR12	5500 (379)	2.34 (59.4)	1.68 (42.7)	3/4 MNPT
1 NPT	METH161162	S1212U70	METR16	5000 (345)	2.74 (69.6)	1.99 (50.5)	1 MNPT

Dimensions: inch (mm)  
Pressure Rating: psi (bar)

\*Optional seal materials include V = FKM, E = EPDM, and B = Buna-N - Example: MET021022V = FKM


\*\*Other terminations in metric / BSPP may be available. Contact factory.

**Port Specifications:** NPT per ISO J476 or ANSI B1.20



**DON'T SEE A SOLUTION FOR YOUR APPLICATION?** Submit a custom application form and drawing to [fastsales@fastestinc.com](mailto:fastsales@fastestinc.com) or to your local distributor.

# MET / EXTERNAL CONNECTIONS / NPT THREADS (continued)



Ordering Information					Dimensions		
Connects To	Part Number	Main Seal Package(5)	Rebuild Kit	Pressure Rating	A	B	T**

**NPT** | Swivel Style for Thin Walled Threaded Pipe

1/4 NPT	MET041042PT	METB04PT	METR04	750 (52)	1.74 (44.2)	0.93 (23.6)	1/4 NPTM
3/8 NPT	MET061062PT	METB06PT	METR06		1.78 (45.2)	1.20 (30.5)	3/8 NPTM
1/2 NPT	MET081082PT	METB08PT	METR08		2.05 (52.1)	1.36 (34.5)	1/2 NPTM
3/4 NPT	MET121122PT	METB12PT	METR12		2.34 (59.4)	1.68 (42.7)	3/4 NPTM
1 NPT	MET161162PT	METB16PT	METR16		2.74 (69.6)	1.99 (50.5)	1 NPTM
1-1/4 NPT	MET201202PT	METB20PT	METR20		3.27 (80.1)	2.37 (60.2)	1 1/4 NPTM
1-1/2 NPT	MET241161*	METB24PT	METR24		3.27 (80.1)	2.50 (63.5)	1 NPTM
2 NPT	MET321161*	METB32PT	METR32	2.53 (64.3)	3.00 (76.2)		
2-1/2 NPT	MET401161*	METB40PT	METR40	500 (35)	2.54 (64.5)	3.40 (86.4)	
3 NPT	MET481161*	METB48PT	METR48	2.61 (66.3)	4.25 (108.0)		

**NPT** | Cap Style

1/8 NPT	MET021C	S1105U70	METR02	5000 (345)	0.83 (21.1)	0.80 (20.3)	N/A (Cap Style No Termination Port)
1/4 NPT	MET041C	S1108U70	METR04		0.88 (22.4)	0.93 (23.6)	
3/8 NPT	MET061C	S1110U70	METR06	4000 (276)	0.90 (22.9)	1.20 (30.5)	
1/2 NPT	MET081C	S1112U70	METR08		0.97 (24.6)	1.36 (34.5)	
3/4 NPT	MET121C	S1115U70	METR12		1.08 (27.4)	1.68 (42.7)	
1 NPT	MET161C	S1112U70	METR16		1.26 (32.0)	1.99 (50.5)	



Dimensions: inch (mm)  
Pressure Rating: psi (bar)

\*Optional seal materials include V = FKM, E = EPDM, and B = Buna-N - Example: MET041042PTV = FKM

\*\*Other terminations in metric / BSPP may be available. Contact factory.

**Port Specifications:** NPT per ISO J476 or ANSI B1.20

# MET / EXTERNAL CONNECTIONS / SAE 37° & 45° FLARE THREADS



Ordering Information					Dimensions		
Connects To	Part Number*	Main Seal Package (5)	Rebuild Kit	Pressure Rating	A	B	T**

**SAE 37° FLARE | Swivel Style**

-6 [9/16-18]	MET069040	S1012B70	METR06	5000 (345)	1.82 (46.2)	1.20 (30.5)	-4 [7/16-20] (male)
-8 [3/4-16]	MET089060	S1015B70	METR08	4000 (276)	1.90 (48.3)	1.38 (35.1)	-6 [9/16-18] (male)
-10 [7/8-14]	MET109080	S1016B70	METR08		2.25 (57.2)	1.51 (38.4)	-8 [3/4-16] (male)
-12 [1-1/16-12]	MET129100	S1018B70	METR12	1000 (69)	2.52 (64.0)	1.70 (43.2)	-10 [7/8-14] (male)
-16 [1-5/16-12]	MET169120	S1020B70	METR16		2.70 (68.6)	1.99 (50.6)	-12 [1-1/16-12] (male)
-20 [1-5/8-12]	MET209160	S1024U70	METR20		3.21 (81.5)	2.37 (60.2)	-16 [15/16-12] (male)
-24 [1-7/8-12]	MET249200	S1029B70	METR24	750 (52)	3.38 (85.9)	2.50 (63.5)	-20 [1-5/8-12] (male)
-32 [2-1/2-12]	MET329240	S1227B70	METR32AN		3.49 (88.6)	3.25 (82.6)	-24 [1-7/8-12] (male)

**SAE 37° FLARE | Swivel Style for High Pressure**

-4 [7/16-20]	METH049040	S20700270B70	METR049	10,000 (689)	1.76 (44.7)	0.95 (24.1)	-4 [7/16-20] (male)
-6 [9/16-18]	METH069060	S1012B70	METR06		1.82 (46.2)	1.20 (30.5)	-6 [9/16-18] (male)
-8 [3/4-16]	METH089080	S1015B70	METR08	6500 (433)	2.00 (50.8)	1.38 (35.1)	-8 [3/4-16] (male)
-10 [7/8-14]	METH109100	S1016B70	METR08		2.35 (59.7)	1.51 (38.4)	-10 [7/8-14] (male)
-12 [1-1/16-12]	METH129120	S1018B70	METR12	6500 (433)	2.52 (64.0)	1.70 (43.2)	-12 [1-1/16-12] (male)
-16 [1-5/16-12]	METH169160	S1120B70	METR16		2.74 (69.6)	1.99 (50.6)	-16 [15/16-12] (male)

**SAE 37° FLARE | Cap Style**

-4 [7/16-20]	MET049C	S120700270B70	METR049	5000 (345)	0.88 (22.4)	0.95 (24.1)	N/A
-6 [9/16-18]	MET069C	S1012B70	METR06		0.90 (22.9)	1.20 (30.5)	(Plug Style No Termination Port)
-8 [3/4-16]	MET089C	S1015B70	METR08	4000 (276)	0.97 (24.6)	1.38 (35.1)	

**SAE 45° FLARE | Swivel Style (per SAE J512 or J513)**

-4 [7/16-20]	MET04A042B	S20600246B70	METR049	5000 (345)	1.76 (44.7)	0.95 (24.1)	1/4 MNPT
-6 [5/8-18]	MET06A062N	S1012N70	METR06A		1.80 (45.7)	1.18 (30.0)	3/8 MNPT
-8 [3/4-16]	MET08A082N	S1014N70	METR08A	4000 (276)	2.10 (53.3)	1.31 (33.3)	1/2 MNPT
-10 [7/8-14]	MET10A082N	S1015N70	METR10A		2.26 (57.4)	1.51 (38.4)	
-12 [1-1/16-14]	MET12A122N	S1018N70	METR12A		2.54 (64.5)	1.70 (43.2)	3/4 MNPT

Dimensions: inch (mm)  
Pressure Rating: psi (bar)

\*Optional seal materials include V = FKM, E = EPDM, and B = Buna-N - Example: MET069040V = FKM

\*\*Other terminations in metric / BSPP may be available. Contact factory.


**Port Specifications:** SAE 37° & 45° FLARE THREADS per SAE J514 or ISO 12151-5



**DON'T SEE A SOLUTION FOR YOUR APPLICATION?** Submit a custom application form and drawing to [fastsales@fastestinc.com](mailto:fastsales@fastestinc.com) or to your local distributor.

# MET / EXTERNAL CONNECTIONS / BSPP (G) THREADS

Swivel Style (per ISO 228 or BS 2779)  
Cap Style (per ISO 228 or BS 2779)



Ordering Information					Dimensions		
Connects To	Part Number	Main Seal Package (5)	Rebuild Kit	Pressure Rating	A	B	T**

## BSPP (G) | Swivel Style

1/8 BSPP (G)	MET025022	S1105U70	METR02	5000 (345)	1.62 (41.1)	0.80 (20.3)	1/8 NPT
1/4 BSPP (G)	MET045042	S1108U70	METR04		1.63 (41.4)	0.93 (23.6)	1/4 NPT
3/8 BSPP (G)	MET065062	S1110U70	METR06	4000 (276)	1.31 (33.3)	1.20 (30.5)	3/8 NPT
1/2 BSPP (G)	MET085082	S1112U70	METR08		1.46 (37.1)	1.36 (34.5)	1/2 NPT
3/4 BSPP (G)	MET125122	S1115U70	METR12		2.35 (59.7)	1.70 (43.2)	3/4 NPT
1 BSPP (G)	MET165162	S1212U70	METR16		2.74 (69.6)	1.99 (50.6)	1 NPT

## BSPP (G) | Cap Style

1/8 BSPP (G)	MET025C	S1105U70	METR02	5000 (345)	0.83 (21.1)	0.80 (20.3)	N/A (Plug Style No Termination Port)
1/4 BSPP (G)	MET045C	S1108U70	METR04		0.88 (22.4)	0.93 (23.6)	
3/8 BSPP (G)	MET065C	S1110U70	METR06	4000 (276)	0.90 (22.9)	1.20 (30.5)	
1/2 BSPP (G)	MET085C	S1112U70	METR08		0.97 (24.6)	1.36 (34.5)	
3/4 BSPP (G)	MET125C	S1116U70	METR12	4000 (276)	1.08 (27.3)	1.68 (42.7)	

Dimensions: inch (mm)  
Pressure Rating: psi (bar)


\*Optional seal materials include V = FKM, E = EPDM, and B = Buna-N - Example: MET025022V = FKM

\*\*Other terminations in metric / BSPP may be available. Contact factory.

**Port Specifications:** BSPP (G) per ISO 228 or BS 2779

# MET / EXTERNAL CONNECTIONS / BSPT THREADS

Swivel Style  
Cap Style



Ordering Information					Dimensions		
Connects To	Part Number	Main Seal Package (5)	Rebuild Kit	Pressure Rating	A	B	T**
<b>BSPT   Swivel Style</b>							
1/8 BSPT	MET025T022	S1105U70	METR02	5000 (345)	1.62 (41.1)	0.80 (20.3)	1/8 NPT
1/4 BSPT	MET045T042	S1108U70	METR04		1.63 (41.4)	0.93 (23.6)	1/4 NPT
3/8 BSPT	MET065T062	S1110U70	METR06	4000 (276)	1.31 (33.3)	1.20 (30.5)	3/8 NPT
1/2 BSPT	MET085T082	S1112U70	METR08		1.46 (37.1)	1.36 (34.5)	1/2 NPT
3/4 BSPT	MET125T122	S1115U70	METR12		2.35 (59.7)	1.70 (43.2)	3/4 NPT
1 BSPT	MET165T162	S1212U70	METR16		2.74 (69.6)	1.99 (50.6)	1 NPT

<b>BSPT   Cap Style</b>							
1/8 BSPT	MET025TC	S1105U70	METR02	5000 (345)	0.83 (21.1)	0.80 (20.3)	N/A
1/4 BSPT	MET045TC	S1108U70	METR04		0.88 (22.4)	0.93 (23.6)	
3/8 BSPT	MET065TC	S1110U70	METR06	4000 (276)	0.90 (22.9)	1.20 (30.5)	(Plug Style No Termination Port)
1/2 BSPT	MET085TC	S1112U70	METR08		0.97 (24.6)	1.36 (34.5)	

Dimensions: inch (mm)  
Pressure Rating: psi (bar)

\*Optional seal materials include V = FKM, E = EPDM, and B = Buna-N - Example: MET025T022V = FKM

\*\*Other terminations in metric / BSPP may be available. Contact factory.

**Port Specifications:** BSPT per ISO 228 or BS 2779; per ISO 7 or BS 21



**DON'T SEE A SOLUTION FOR YOUR APPLICATION?** Submit a custom application form and drawing to [fastsales@fastestinc.com](mailto:fastsales@fastestinc.com) or to your local distributor.